

PHS MS Hybrid Sealant

PHS MS Hybrid Sealant is a high performance, flexible and stable single component adhesive and sealant based on hybrid polymer technology. It is a single part, moisture-cure adhesive/sealant that requires no mixing or activating and provides excellent adhesion properties.

PHS MS Hybrid Sealant is used for general purpose bonding on a wide variety of materials as well as for applications such as sealing of seams and joints in construction (including glass and mirror constructions) and the sealing of interior and exterior expansion and connecting joints.

PHS MS Hybrid Sealant is suitable for following applications:

- Boat / ship building (decks, doors, panels etc.).
- Automotive industry (car body assembly, buses, containers etc.). Window and door frame perimeter joints.
- Vehicle conversion, caravans.
- Construction and building joints including door and concrete joints. Bonding applications in metal constructions and for mounting vibrating parts.
- Good adhesion to many substrates (including PVC, EPDM, glass, wood, stone).



Advantages

- Multi-purpose adhesive sealant.
- Single component - no need to mix and easy to use.
- Isocyanate, solvent and silicone free.
- Chemically neutral.
- Suitable for bonding glass and mirrors (in accordance with DIN1238).
- Good resistance to tear and weather.
- Elastic compound which accepts movement.
- Excellent resistance to chemicals and seawater.
- Can be over painted when fully cured (in accordance with DIN52452 Part 4).

Technical Data

Base	Hybrid Polymer
Colour	Black
Consistency	Tixotropic Paste
Specific Gravity (20C)	1.50
Skin Formation Time (20C to 50%RH)	approx. 40 minutes
Cure Rate (20C to 50%RH)	3mm / 24 hours
Temperature Resistance	-40°C to +90°C
Application Resistance	+5°C to +40°C
Compatibility with Paint (after curing)	water based paints-Yes
Coverage (per 300ml cartridge)	15m (5mm beads)
	3m (10mm beads)

Passive House Systems IE
P31 W950, Ballincollig, Cork, Ireland
tel. (+353) 021 4872664
www.passivehousesystems.ie

Passive House Systems UK
CM16 6th, Epping, Essex, UK
tel. (+44) 0333 880 2347
www.passivehousesystems.co.uk

Passive House Systems products are used by diverse customer base for a wide range of technical and industrial applications. The demands made on our products vary considerably from application to application. We strongly advise users to test the products suitability for their own particular requirement.

All data and recommendations contained in this Technical Datasheet are based on our own test results and practical experience and are aimed at helping customers select the appropriate product. This information is provided without liability. We reserve the right to change the technical specification without prior notice. Samples are available free of charge. Our sales team are available to help support all technical specifications for our products.